

VEGAS IP20 DRIVERS



12V NON-DIMMABLE & DIMMABLE DRIVERS

- IP20 for indoor applications only
- Constant voltage driver for use with 12V VEGAS strip range only
- Dimmable with traditional wall mounted dimmer switch
- Dimmable drivers compatible with selected leading and trailing edge dimmers.- see page 57
- Minimum strip length to ensure proper dimming as per table below



12V NON-DIMMABLE DRIVERS					
	15W	30W	60W	100W	180W
	RVA1512-PSU	RVA3012-PSU	RVA6012-PSU	RVA10012-PSU	RVA18012-PSU
Total Power (W:)	15	30	60	100	180
Voltage:	12VDC	12VDC	12VDC	12VDC	12VDC
IP:	20	20	20	20	20
Length (mm):	103	149	170	180	195
Width (mm):	35.5	40	44	65	67
Height (mm):	16	27	28	31	31
Weight (kg):	0.04	0.12	0.22	0.37	0.41



12V DIMMABLE DRIVERS (DIMMABLE WITH TRADITIONAL WALL MOUNTED DIMMER SWITCH)			
	30W	50W	75W
	RVA3012DU-PSU	RVA5012DU-PSU	RVA7512DU-PSU
Total Power (W:)	30	50	75
Voltage:	12VDC	12VDC	12VDC
IP:	20	20	20
Length (mm):	158	158	170
Width (mm):	46	46	56
Height (mm):	18	18	31
Weight (kg):	0.12	0.21	0.3

MINIMUM 12V STRIP LENGTH TO ENSURE PROPER DIMMING	
RVA3012DU-PSU	1m
RVA5012DU-PSU	3m
RVA7512DU-PSU	5m

VEGAS IP20 DRIVERS

24V NON-DIMMABLE & DIMMABLE DRIVERS

- IP20 for indoor applications only
- Constant voltage driver for use with 24V VEGAS strip range only
- Dimmable with traditional wall mounted dimmer switch
- Dimmable drivers compatible with selected leading and trailing edge dimmers.- see page 57
- Minimum strip length to ensure proper dimming as per table below



24V NON-DIMMABLE DRIVERS							
	15W	30W	60W	100W	150W	250W	320W
	RVA1524-PSU	RVA3024-PSU	RVA6024-PSU	RVA10024-PSU	RVA15024-PSU	RVA25024-PSU	RVA32024-PSU
Total Power (W:)	15	30	60	100	150	250	320
Voltage:	24VDC	24VDC	24VDC	24VDC	24VDC	24VDC	24VDC
IP:	20	20	20	20	20	20	20
Length (mm):	103	149	170	180	180	195	215
Width (mm):	35	40	45	65	66	62	78
Height (mm):	16	27	28	31	31	36	35
Weight (kg):	0.04	0.12	0.22	0.37	0.41	0.42	0.44

24V DIMMABLE DRIVERS (DIMMABLE WITH TRADITIONAL WALL MOUNTED DIMMER SWITCH)			
	30W	50W	75W
	RVA3024DU-PSU	RVA5024DU-PSU	RVA7524DU-PSU
Total Power (W:)	30	50	75
Voltage:	24VDC	24VDC	24VDC
IP:	20	20	20
Length (mm):	158	158	170
Width (mm):	46	46	56
Height (mm):	18	18	31
Weight (kg):	0.12	0.21	0.3



MINIMUM 24V STRIP LENGTH TO ENSURE PROPER DIMMING	
RVA3024DU-PSU	1m
RVA5024DU-PSU	3m
RVA7524DU-PSU	3m