

PURO SLIM

PUROSL13W-250R
SAP CODE: 2002532


Minimalist design, maximum impact

The PURO SLIM is a sleek, IP54-rated LED ceiling light designed for optimal performance in general lighting applications. Its slim 26mm profile and even light distribution create a modern, minimalist aesthetic. With adjustable colour temperature, three size variations and available in black and white finishes, the PURO SLIM adapts seamlessly to diverse residential settings.


APPLICATIONS

Bedrooms, Lounge Room, Dining Area, Laundry, Hallways, Staircase, Walk-in Wardrobes, Garage, Education Facilities, Hotel Common Areas, Hotel Rooms, Storage Rooms, Temporary Installations

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd
— C0/180,112.9
— C90/270,112.4

Photometric diagram shown is for 4000 K output.

KEY INFORMATION

Power	13 W
Lumen Output	1196 / 1290 / 1271 lm
Mounting Type	Surface Mount
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP54
IK Rating	Not Applicable
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA10 Terminals
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	99.83 / 111.09 / 106.14 lm/W
CCT	3000 / 4000 / 5700 K
CRI	> 80
SDCM	< 5
UGR	Not Applicable
Beam Angle	110°
Flicker-Free	Yes
Projected Lifespan	>85,000hrs @ Ta 45°C (L80)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Polypropylene
Diffuser Material	PMMA
Rebate Scheme Approvals	
Weight	0.47 kg
Dimensions	Ø 244 x 26 mm