



TRIPROOF *Weatherproof LED Batten*

A robust outdoor/indoor IK08 impact resistant LED batten with Tritone switchable colour temperature.

Description

The perfect LED replacement for conventional weatherproof battens, the robust TRIPROOF offers IP65 weatherproof and IK08 impact rating. Intellisensor motion sensor with corridor function and dual power selection further enhance energy savings and Lithium Iron Phosphate (LiFePO4) battery version is available where emergency lighting is required.

Key Features

- *Selectable colour temperature - 4000K, 5000K and 6500K*
- *Dual power selection available in 1200mm length only*
- *Quick and easy installation*
- *Intellisensor motion sensor with corridor function available*
- *Lithium Iron Phosphate (LiFePO4) battery emergency version available*

Applications

Residential, Schools, Factories, Carpark, Stairwells, Public Areas



IP65



IK08



50,000hr



5yr



4yr
(battery only)



HACCP



TRITONE
colour changeable

TRIPROOF *Weatherproof LED Batten*



NOMINAL LENGTH 600MM

STANDARD MODE				LOW POWER MODE				EMERGENCY SPECIFICATION				
FEATURE	POWER	LUMEN	lm/W	POWER	LUMEN	lm/W	CCT	WEIGHT	EMERGENCY CLASSIFICATION	BATTERY TYPE	SAP CODE	PRODUCT CODE
	20W	1850 lm	93 lm/W	N/A	N/A	N/A	4000K	2.00 kg	-	-	2001164	TRIPROOF 20W06-TRI
		1990 lm	100 lm/W				5000K					
		1850 lm	93 lm/W				6500K					
Emergency	20W	1850 lm	93 lm/W	N/A	N/A	N/A	4000K	2.20 kg	C0=D50, C90=D32	LiFePO4	2001165	TRIPROOF 20W06-TRI-EM*
		1990 lm	100 lm/W				5000K					
		1850 lm	93 lm/W				6500K					

NOMINAL LENGTH 1200MM

STANDARD MODE				LOW POWER MODE				EMERGENCY SPECIFICATION				
FEATURE	POWER	LUMEN	lm/W	POWER	LUMEN	lm/W	CCT	WEIGHT	EMERGENCY CLASSIFICATION	BATTERY TYPE	SAP CODE	PRODUCT CODE
	40W	4090 lm	102 lm/W	20W	2230 lm	112 lm/W	4000K	2.00 kg	-	-	2001168	TRIPROOF 20/40W12-TRI
		4410 lm	110 lm/W		2250 lm	113 lm/W	5000K					
		4050 lm	101 lm/W		1970 lm	99 lm/W	6500K					
Emergency	40W	4090 lm	102 lm/W	20W	2230 lm	112 lm/W	4000K	2.20 kg	C0=D63, C90=D32	LiFePO4	2001066	TRIPROOF 20/40W12-TRI-EM*
		4410 lm	110 lm/W		2250 lm	113 lm/W	5000K					
		4050 lm	101 lm/W		1970 lm	99 lm/W	6500K					
Intellisensor	40W	4090 lm	102 lm/W	N/A	N/A	N/A	4000K	2.00 kg	-	-	2001067	TRIPROOF 40W12-TRI-SS
		4410 lm	110 lm/W				5000K					
		4050 lm	101 lm/W				6500K					
Intellisensor Emergency	40W	4090 lm	102 lm/W	N/A	N/A	N/A	4000K	2.20 kg	C0=D63, C90=D32	LiFePO4	2001068	TRIPROOF 40W12-TRI-SS-EM*
		4410 lm	110 lm/W				5000K					
		4050 lm	101 lm/W				6500K					

*TRIPROOF emergency version is IP54.

NOMINAL LENGTH 1500MM

STANDARD MODE				LOW POWER MODE				EMERGENCY SPECIFICATION				
FEATURE	POWER	LUMEN	lm/W	POWER	LUMEN	lm/W	CCT	WEIGHT	EMERGENCY CLASSIFICATION	BATTERY TYPE	SAP CODE	PRODUCT CODE
	60W	5600lm	93 lm/W	N/A	N/A	N/A	4000K	3.50 kg	-	-	2001170	TRIPROOF 60W15-TRI
		6000lm	100 lm/W				5000K					
		5700lm	95 lm/W				6500K					
Emergency	60W	5600lm	93 lm/W	N/A	N/A	N/A	4000K	3.70 kg	C0=D50, C90=D32	LiFePO4	2001171	TRIPROOF 60W15-TRI-EM
		6000lm	100 lm/W				5000K					
		5700lm	95 lm/W				6500K					